

ilex³²

Direct connect to C-arm workstations and cameras
Digital connectivity with no scaling or conversion required*

Designed for use as a large table side monitor,
the ilex 32 combines practical features with easy use.

- 32" high definition monitor with dual DVI, SDI, SOG, S-Video inputs
- Rugged counter-balanced base with minimal footprint
- Single, side-by-side or picture-in-picture imaging modes
- Typical video input sources: C Arm, hemodynamics and ultrasound
- Accessories Included:
 - Accessory basket
 - Cable hook
 - Transport handle

Stand

- Five casters, front two lockable
- Adaptable column with built-in wire-way and vertical accessory attachment rails
- Heavy duty VESA mount with tilt
- Cables included

Monitor

- 32" (81cm) high-bright LED monitor, 1920 x 1080 pixel resolution
- Width: 30.31" (77cm) x Height: 27.64" (70cm)
- Aspect ratio - 16 x 9
- Contrast Ratio 1300:1
- Pixel Pitch .27 (W) x .27 (H)
- Surface luminance 450 cd/m²
- Medical display, color corrected with stabilized brightness and 178° viewing angle



32" (81cm) high-bright LED monitor

idi

Image Diagnostics, Inc.
Safety, Simplicity, Quality



A veteran-owned company

Image Diagnostics, Inc., 310 Authority Drive, Fitchburg, MA 01420
Tel: 978-829-0009 ImageDiagnostics.com D000-1997D